

ROHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

Pin No.	Pin assignment	Pin No.	Pin assignment
1	DAT2	6	VSS
2	CD/DAT3	7	DAT0
3	CMD	8	DAT1
4	VDD		
5	CLK	G	

NOTE:

- ELECTRICAL CHARACTERISTICS
 - VOLTAGE RATING: 10V DC.
 - CURRENT RATING: 0.5 A.
 - CONTACT RESISTANCE: 80 milliohms MAX.
 - INSULATION RESISTANCE: 1000 Megohms MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
- MECHANICAL CHARACTERISTICS
 - RETENTION FORCE: 100gf MIN./PIN.
 - DURIBILITY: 5000 CYCLES.
 - SALT SPRAY: 24H.
 - OPERATING TEMPERATURE: -40°C~85°C.
 - ROHS 2002/95/EC COMPLIANT.
 - MPQ : 1500PCS/REEL.

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	BROKEN	2015.12.08

C	SHELL	1	SUS 201	Ni PLATING
B	CONTACT	8	C2680	Gold Flash on Contact Area Tin plated on Solder tail All over Nickel Plated.
A	HOUSING	1	LCP	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: ANGLES:

X : ±0.5 X : ±2°
X.X : ±0.3 X.X : ±1°
X.XX : ±0.2

TITLE: T-FLASH CONN HING TYP 1.5H
PART NO. 1060801GR205
DWG BROKEN 2015.12.08
CHKD
APVD
SCALE 1:1 UNIT: mm
SIZE: A4 SHEET: 10F1 REV: A

CUSTOMER COPY

TETULL CORPORATION