

ROHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

NOTE:

1. ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING: 10V DC.
 - 1-2. CURRENT RATING: 0.5 A.
 - 1-3. CONTACT RESISTANCE: 80 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 1000 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
 - 2-1. RETENTION FORCE: 100gf MIN./PIN.
 - 2-2. DURABILITY:5000 CYCLES.
 - 3. SALT SPRAY: 24H.
 - 4. OPERATING TEMPERATURE:-40°C~85°C.
 - 5. ROHS 2002/95/EC COMPLIANT.
 - 6. MPQ : 1800PCS/REEL

Pin No.	NAME
1	DATE
2	CD/DAT3
3	CMD
4	VDD
5	CLK
6	VSS
7	DAT0
8	DAT1

RECOMMENDED P.C.B LAYOUT(TOP VIEW)
GENERAL TOLERANCE ±0.05

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	JAMES	2010.03.29
B	MODIFY	BROKEN	2015.04.21

C	SHELL	1	STAINLESS STEEL 0.15t	NI PLATING
B	CONTACT	8	COPPER ALLOY 0.15t	Gold Flash on Contact Area Tin plated on Solder tail All over Nickel Plated.
A	HOUSING	1	HIGH-TEMPERATURE PLASTIC U94-10	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: ANGLES:

X : ±0.5 X : ±2
X.X : ±0.3 X.X : ±1'
X.XX : ±0.2

CUSTOMER COPY

TITLE: T-FLASH CONN. 8P SIMPLE SOCKET 1.5H

PART NO. 1060813PT002

DWG BROKEN 2015.04.21

CHKD

APVD

SCALE 1:1

UNIT: mm

SIZE: A4

SHEET: 10F1

REV: B

TETULL CORPORATION