

ROHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TETULL PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TETULL LTD.

REV/ECN NO OR DESCRIPTION	REVISED	DATE
A PRODUCT RELEASE	MKE	2019.10.09
B MODIFY	BEKEM	2020.05.13

NOTE:

- ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING:30V AC
 - 1-2. CURRENT RATING:2.0A
 - 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 100 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
- MECHANICAL CHARACTERISTICS
 - 2-1. MATING&UNMATING FORCE: 0.7kgf~3.5kgf
 - 2-2. DURIBILITY:10000CYCLES
 - 3. SALT SPRAY: 24H
 - 4. OPERATING TEMPERATURE:-40°C~85°C
 - 5. RoHS 2002/95/EC COMPLIANT.
 - 6. CRITICAL DIMENSIONS : ▽

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
D	PCB	1	FR4-1	T-045
C	SHELL	1	SPOC 0.30t	NI
B	CONTACT	10	C5191 0.20t	Gold Flash On Contact Area Tin plated on Solder tail All over Nickel Plated.
A	HOUSING	1	LCP	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: ANGLES:

X :±0.5 X :±2°
 X.X :±0.3 X.X :±1'
 X.XX :±0.2

TITLE: MINI 10P公头连接器脚型L=17.0 (10点)外形脚固定

PART NO.	DWG	CHND	APVD
1031002GR075	BROKEN		

SCALE 1:1 UNIT: mm

SIZE: A4 SHEET: 10F1 REV: B

CUSTOMER COPY

TETULL CORPORATION